



The Demag SpeedHoist is specially designed for fast load handling applications with loads weighing up to 80 kg or 160 kg. The D-Grip control handle enables the load to be guided particularly easily and precisely, in exactly the same way as you move your hand.

## DEMAG SPEEDHOIST OFFERS OUTSTANDING BENEFITS

- Very fast lifting and lowering motions (up to 70 m/min or 35 m/min)
- Infinitely variable speed control by moving the control handle up or down
- Quick-release coupling to accommodate various load handling attachments
- Individually adjustable dynamics (speed and acceleration) by means of rotary coding switches, programming device or PC
- Integrated elapsed operating time counter
- Diagnosis support in the form of a fl ashing error code displayed on the handle and by means of a terminal and error memory
- Switchover between two different maximum speeds

- Free digital output configuration to control external devices
- Temperatures of motor and electronic equipment monitored
- Lifting and lowering motion cut-off in the highest and lowest hook positions
- Overload cut-off
- Designed for indoor operation under normal ambient conditions and temperatures from 0 to 40 °C

D-SH 80/D-SH 160 technical data		
Load capacity	80 kg	160 kg
FEM Groupe	1 Am	
Hoist speed	up to 70 m/min	up to 35 m/min
Lifting height	2.2 m	
Supply voltage	400 V	
Frequency	50 Hz	

## **DEMAG CRANES & COMPONENTS GMBH**

Wetter Site Ruhrstraße 28 58300 Wetter, Germany

**E** info@demagcranes.com

**T** +49 2335 92-0

**F** +49 2335 92-7676 www.demagcranes.com

DEMAG

0818 EN/DE 213 125 44 700 IS 852 No liability for errors or omissions. Subject to change. Printed in Germany D/310818/PDF