Uncompromisingly cost-effective



Demag DC-Com special chain hoist

100% longer service life – 50% higher duty factor



Uncompromising engineering – and price



Our **DC-Com special chain hoist** provides you with a Demag brand quality product with comprehensive features. Rated for a long service life and ideally suited for everyday needs. Based on our tried-andtested DC-Com range, this special model boasts a high FEM classification and high duty factor.

All aluminium housing components have high-quality powder coating.

Available as a solo hoist or as a push-travel or electric-travel hoist unit.

Take advantage of our preferential series and its attractive price.

- 24 V contactor control
- High level of safety thanks to brake arranged in front of the slipping clutch in the load-bearing arrangement
- Reliable operation from -20 °C to +45 °C without any reduction in the duty factor, operation up to 60 °C also possible.
- Operating limit switches (upper and lower hook positions)
- Elapsed operating time counter
- Always convenient with main and creep lifting speeds
- Five types for load capacities up to 2,000 kg
- 4 m or 5 m hook path as standard
- Interface for electric travel
- Gearbox maintenance-free for up to 10 years

Load capacity	Chain hoist	Reeving	Group of mecha- nisms	Lifting speeds [m/min]	
[kg]	Туре		FEM/ISO	at 50 Hz	at 60 Hz
125	DC-ComA 1-125	1/1	3m / M6	8,0/2,0	9,6/2,4
250	DC-ComA 2-250		2m / M5	6,0/1,5	7,2/1,8
500	DC-ComA 5-500		2m / M5	4,5/1,1	5,4/1,3
1.000	DC-ComA 10-1000		2m / M5	4,0/1,0	4,8/1,2
2.000	DC-ComA 10-2000	2/1	2m / M5	4,0/1,0	4,8/1,2

- For all sizes: 60 % duty cycle, available in H4 and H5.
- Sizes 1-125, 2-250, 5-500, 10-1,000 kg with H4 available from stock.

Demag

Cranes & Components GmbH Wetter Site

 Ruhrstrasse 28

 \$8300 Wetter, Germany

 E
 info@demagcranes.com

 T
 +49 2335 92 0

 F
 +49 2335 92 7676

 www.demagcranes.com

